

Connector AM-TOP®
Part no. 523




- screw terminals
- single part body
- cable gland and sealing
- strain relief and protection against kinking

Technical specifications

| | |
|---------------------------|-----------------|
| Ampere | 32 A |
| Poles | 3 p |
| Voltage | 400 V |
| Clock position | 9 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 44 |
| Weight | 313 g |
| Declaration of Conformity | VDE, EAC, CQC |

Drawing



| Drawing 3 MB 63 | Amp. Poles | 16 | | | 32 | | |
|--------------------------|---------------|------|------|------|-----|-----|-----|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 162 | 165 | 167 | 209 | 209 | 208 |
| | b | 60 | 68 | 76 | 82 | 82 | 89 |
| | h | 83 | 92 | 98 | 100 | 100 | 108 |
| | y | 14.5 | 16 | 16 | 22 | 22 | 22 |
| Terminal for cond. cross | | 1 | 1 | 1 | 2.5 | 2.5 | 2.5 |
| section (mm²) min.-max. | | —2.5 | —2.5 | —2.5 | —6 | —6 | —6 |