

**Plug PowerTOP® Xtra**  
Part no. 13102




- screw terminals
- rubberised grip area
- frame terminals
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and sealing
- strain relief and protection against kinking
- enclosure with thread lock
- two safety slides

Technical specifications

|                           |   |
|---------------------------|---|
| Ampere                    | 63 A  |
| Poles                     | 3 p   |
| Voltage                   | 230 V   |
| Clock position            | 6 h   |
| Hertz                     | 50-60 Hz  |
| Connection technology     | Screw terminals   |
| Contact                   | highly heat resistant contact carrier, nickel plated contacts |
| Protection type           | IP 44   |
| Weight                    | 682 g   |
| Declaration of Conformity | VDE, EAC, CQC   |

Drawing



| Drawing<br>2 MB 226                  | Amp.<br>Poles | 63  |     |     |
|--------------------------------------|---------------|-----|-----|-----|
|                                      |               | 3   | 4   | 5   |
| Dim. in mm                           | a             | 250 | 250 | 250 |
|                                      | b             | 90  | 90  | 90  |
|                                      | y             | 36  | 36  | 36  |
| Terminal for cond. cross             |               | 6   | 6   | 6   |
| section (mm <sup>2</sup> ) min.-max. |               | —16 | —16 | —16 |