

## **Connector AM-TOP®**

Part no. 519




- screw terminals

- single part body cable gland and sealing strain relief and protection against kinking

## **Technical specifications**

Ampere	16 A
Poles	5 p
Voltage	230 V
Clock position	9 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Weight	240 g
Declaration of Conformity	VDE, EAC, CQC

## Drawing



Diawing Amp.		10			] 32		
Poles	3	4	5	3	4	5	
а	162	165	167	209	209	208	
b	60	68	76	82	82	89	
h	83	92	98	100	100	108	
у	14.5	16	16	22	22	22	
Terminal for cond. cross		1	1	2.5			
nmax.	—2.5	<b>—</b> 2.5	—2.5	-6	<b>—</b> 6	-6	
	Poles a b h y	Poles         3           a         162           b         60           h         83           y         14.5	Poles         3         4           a         162         165           b         60         68           h         83         92           y         14.5         16           d. cross         1         1	Poles         3         4         5           a         162         165         167           b         60         68         76           h         83         92         98           y         14.5         16         16           d. cross         1         1         1	Poles         3         4         5         3           a         162         165         167         209           b         60         68         76         82           h         83         92         98         100           y         14.5         16         16         22           d. cross         1         1         1         2.5	Poles         3         4         5         3         4           a         162         165         167         209         209           b         60         68         76         82         82           h         83         92         98         100         100           y         14.5         16         16         22         22           d. cross         1         1         1         2.5         2.5	